



**LONG LASTING FLEXIBILITY**

# FIBACRYL®

## FLEXIBLE FILLER FOR CRACKS



- ▶ **MOVES WITH THE SUBSTRATE**
- ▶ **WILL NOT CRACK**
- ▶ **ADHERES TO PAINT WORK**
- ▶ **NO NEED TO SPOT PRIME**
- ▶ **WILL NOT FLASH OR GRIN**

### PURPOSE

Ready to use flexible filler enriched with fibers – Interior and exterior use – Manual application.

### SUBSTRATES

**FIBACRYL®** can be applied on any substrate either unpainted or painted:

- Gypsum plaster, plaster tiles, plasterboards
- Old painted surfaces
- Concrete, cellular concrete
- Cement, breeze blocks, bricks, stones
- Primed woods
- Mortar.

### OVERCOATING

**FIBACRYL®** is to be overcoated by any type of fillers and paints, waterborne or mineral in thin coat, thick plastic wall coverings and waterproof coatings.

### Physical and technical FEATURES

**FIBACRYL®**: Filler in paste form for interior and exterior use made of mineral extracts and selected resin.

- Characterization (NFT 36-005): Family IV Class 4b
- Codification (EN 16566):  $G_3S_2V_0W_0A_0C_0R_0$
- Application thickness: up to 1 cm
- Second coat: once the filler is dry
- Overcoating: 24 to 48 h average time (when fully dry)
- Colour: white
- Adhesion filler/substrate (EN 16566): > 0.8 Mpa

### USE AND STORAGE CONDITIONS

- Application tool: Filling knife or blade.
- Tools cleaning: With water.
- Preservation: product guaranteed 12 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored away from frost and sunlight.

### PACKAGING

- Cartridge of 310 ml
- Tubs : 1-4 L

### RECOMMENDATIONS and care for use

- Do not apply under a temperature < 5 °C and > 35 °C nor under an hygrometry rate over 80 %
- Do not apply on overheated surfaces nor in sun exposure.

### SUBSTRATES PREPARATION

- Substrates to be prepared as per the current trade practices.
- Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS to be referred to

- EN 16566: Coating Fillers for interior and/or exterior works.
- NFT 36-005: Characterization of paint products.
- DTU 59.1 (NFP 74-201): Building paint works.
- DTU 42.1 (NFP 84-404): Façades renovation with polymer-based waterproofing coatings.

### HEALTH AND SAFETY

- No danger tag.
- Very low VOC emissions : < 0,1 %
- Safety data sheets available on [www.toupret.co.uk](http://www.toupret.co.uk)

The data sheet information, especially the guidelines relevant to the application and final use of **FIBACRYL®** are provided in good faith and result from the knowledge of the products and experience of TOUPRET Company. The product is required to be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed under a temperature of 20°C, a hygrometry rate of 50 % and on normal-absorbent substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions



Information on the level of emission of volatile substances in indoor air, presenting a risk of inhalation toxicity, on a class scale from A+ (very low emissions) to C (high emissions).